

## Royalite™ R59

### Fire-rated sheet

#### Product Description

PolyOne's Royalite R59 is a chemical-resistant PVC/ABS fire-rated extruded sheet capable of withstanding high-impact conditions. Coupled with consistent high-quality color, texture, and gloss for a variety of applications including medical device housings and electrical appliances, Royalite R59 can be custom manufactured in gauges from 0.031" to 0.312".

#### Value Solution

With a controlled color match surface and the stiffness of R59, your products can maintain a new look longer and be able to withstand standard working and cleaning conditions. R59's high flexural modulus provides protection from incidental impact and cracking.

Royalite R59 can be utilized in imaging equipment housings, hospital beds, medication carts, and exam tables, and it meets UL requirements for fire rated sheet.

#### UL Listed:

- 94 V-0 at 0.085"
- 94 V-1 at 0.058"
- 94 5VA at 0.085"
- Ball Pressure Test

#### Key Characteristics

The primary features and benefits of Royalite R59 fire-rated sheet are:

- UL Certified and Flame Rated at variety of specs for demanding applications
- High flexural modulus - Creates durable, tough parts that will not deform or strain under stress
- Controlled color match surface
- High Heat Deflection Temperature - passes UL Ball Pressure Test

Passes Federal Motor Vehicle Safety Standard 302



## Markets and End-Use Applications

### Electronics

- Processing terminals, hand-held monitors, and GPS housings

### Healthcare

- Diagnostic imaging equipment and other medical device housings, hospital beds, medication carts and exam tables

### Transportation

- Bus seat backs and other small interior thermoformed parts

**MODERN** *plastics*

*"Setting the Standards in Plastics Distribution"™*

ISO 9001:2008 and ISO 13485:2003 Certified

**88 Long Hill Cross Road, Shelton, Connecticut, 06484 USA**

**ModernPlastics.com - National Toll-Free: 800.243.9696**

**Phone: 203.333.3128 - Fax: 203.333.4625**

**[sales@modernplastics.com](mailto:sales@modernplastics.com)**

**PolyOne™**

*Collaboration. Innovation. Excellence.*

Copyright © 2013, PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.